

TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1

TEST DATE:

14/08/2021 -20/08/2021P/I NO.: IR-20210523-2 dtd:23.05.2021

PRODUCT: 30 KVAR, 440V, 3PH, 50HZ, GAS FILLED MPP TYPE CAPACITOR UNITS.

| Sr. No. | REQUIREMENT /TEST | SPECIFICATIONS | RESULT | REMARK |
|------------|---|--|-------------------------------------|--------|
| 1. | K∨AR Rating | 30 K∨AR | 30 K∨AR | PASS |
| 2. | Voltage Rating | 440 V | 440 V | PASS |
| 3. | Basic Mfd Value (in Mfd) | 246.75 µfd | 246.75 µfd | PASS |
| 4. | Sr. No. of the Capacitor | A883645 | A883645 | PASS |
| 5. | Capacitor Type | GAS FILLED | GAS FILLED | PASS |
| 6. | Frequency | 50 Hz or 60Hz | 50 HZ | PASS |
| 7.1 | Capacitance Measurement and Output Calculation before HV | -5% to +15% for units and banks upto 100 KVAR | 247. 9µfd | PASS |
| 7.2 | Capacitance Measurement and Output Calculation after HV | 0% to 10% for units and banks above 100 KVAR | 247. 9 µfd | PASS |
| 8 | Measurement of the tangent of the loss angle (tan δ) of the capacitor | Shall not exceed value declared by manufacture | 0.49Watt/Kvar | PASS |
| 9 | Voltage tests between Terminals (High Voltage test) | 2.15 x Rated Voltage for 2 sec | Withstood | PASS |
| 10 | Voltage tests between terminals and container | 3 K ∨ AC for 10 Sec | Withstood | PASS |
| 11 | Test of internal discharge device | In 3 min reduces to 75 V or less | 33 sec | PASS |
| 12 | Sealing Test (Leakage Test) | 75°C for 2 Hrs | Not applicable | - |
| 13 | Guide for Installation and Operation of L.T. Power Capacitors General Choice of rated Voltage Operating temperature Installation High Ambient air temperature E valuation of losses S pecial S ervice conditions Over voltages Overload currents S witching and protective devices and connections Capacitors connected to system with Audio frequency remote control EMC Immunity | | The installation manual attached | Pass |

Gat No. 311 Shreem Elec Industrial Estate, Jaysingpur - 416 144,

Dist.: Kolhapur, Maharashtra, (INDIA)

: +91-2322-221021/22/24/45 Fax : +91-2322-221023

e-mail: info@shreemelectric.com : www.shreemelectric.com





TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1

TEST DATE:

14/08/2021 -20/08/2021P/I NO.: IR-20210523-2 dtd:23.05.2021

PRODUCT: 30 KVAR, 440V, 3PH, 50HZ, GAS FILLED MPP TYPE CAPACITOR UNITS.

RATING PLATE DETAILS

| MANUFACTURER | M/s.Shreem Electric Ltd |
|--|-------------------------|
| IDENTIFICATION NUMBER AND MANUFACTURING YEAR | A883645 08-2021 |
| RATED OUTPUT Q _N IN KVAR | 30 Kvar |
| RATED VOLTAGE U _N IN VOLTS | 440 Volt |
| RATED FREQUENCY f _N IN Hz | 50 HZ |
| TEMPERATURE CATEGORY | -40/D |
| DISCHARGE DEVICE | Ext.Fitted |
| REFERENCE OF SELF HEALING DESIGN | MPP (SH) |
| CONNECTION SYMBOL | Delta (Δ) |
| INTERNAL FUSES | No |
| INDICATION OF OVERPRESSURE OR THERMAL DISCONNECTOR | Provided Internally |
| INSULATION LEVEL U _i IN kV | 3 Kv |
| REFERENCE TO IEC 60831 | IEC 60831-1 |



Furthermore, We confirm that the test report is acceptable and the manufacturer's laboratory found to be as qualified.

Manufacturer's Representative

S.A.I. Representative

Shreen Electric Ltt.

Industrial Estate,
Jaysingpur - 416 144,
Dist.: Kolhapur, Maharashtra, (INDIA)

Tel : +91-2322-221021/22/24/45

Fax : +91-2322-221023 e-mail : info@shreemelectric.com

Web

: www.shreemelectric.com