

TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1

TEST DATE:

14/08/2021 -20/08/2021P/I NO.: IR-20210523-2 dtd:23.05.2021

PRODUCT: 12.5 KVAR, 440V, 3PH, 50Hz, NORMAL DUTY MPP TYPE CAPCITOR UNITS.

| Sr. No. | REQUIREMENT /TEST | SPECIFICATIONS | RESULT | REMARK |
|------------|---|---|-------------------------------------|--------|
| 1. | K∨AR Rating | 12.5 K∨AR | 12.5 K∀AR | PASS |
| 2. | Voltage Rating | 440 V | 440 V | PASS |
| 3. | Basic Mfd ∨alue (in Mfd) | 102.81 µfd | 102.81 µfd | PASS |
| 4. | Sr. No. of the Capacitor | A881445 | A881445 | PASS |
| 5. | Capacitor Type | NORMAL DUTY | NORMAL DUTY | PASS |
| 6. | Frequency | 50 Hz or 60Hz | 50H Z | |
| 71. | Capacitance Measurement and Output Calculation before H∨ | -5% to +15% for units and banks upto 100 KVAR | 104.00 μfd | PASS |
| 7.2 | Capacitance Measurement and Output Calculation after HV | 0% to 10% for units and banks above 100 KVAR | 104.00 μfd | PASS |
| 8. | Measurement of the tangent of the loss angle (tan δ) of the capacitor | S hall not exceed value declared by manufacture | 0.48Watt/kVAr | PASS |
| 9. | Voltage tests between Terminals (High Voltage test) | 2.15 x R ated Voltage for 2 sec | Withstood | PASS |
| 10. | Voltage tests between terminals and container | 3 K∨AC for 10 Sec | Withstood | PASS |
| 11. | Test of internal discharge device | In 3 min reduces to 75 V or less | 30 S ec | PASS |
| 12. | Sealing Test (Leakage Test) | 75°C for 2 Hrs | No Leakage | PASS |
| 13. | Guide for Installation and Operation of L.T. Power Capacitors: The installation manual attached herewith General Choice of rated Voltage Operating temperature Installation High Ambient air temperature Evaluation of losses Special Service conditions Over voltages Overload currents Switching and protective devices and connections Capacitors connected to system with Audio frequency remote control EMC Immunity | | The Installation manual attached | Pass |

Gat No. 311 Shreem Elec Industrial Estate Jaysingpur - 416 144, Dist. : Kolhapur, Maharashtra, (INDIA)

+91-2322-221021/22/24/45

Tel : +91-2322-221023 e-mail: info@shreemelectric.com Web : www.shreemelectric.com





TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1

TEST DATE:

14/08/2021 -20/08/2021P/I NO.: IR-20210523-2 dtd:23.05.2021

PRODUCT: 12.5 KVAR, 440V, 3PH, 50Hz, NORMAL DUTY MPP TYPE CAPCITOR UNITS.

RATING PLATE DETAILS

| MANUFACTURER | M/s. SHREEM ELECTRIC LTD |
|--|--------------------------|
| IDENTIFICATION NUMBER AND MANUFACTURING YEAR | A881445 08-2021 |
| RATED OUTPUT Q _N IN KVAR | 12.5Kvar |
| RATED VOLTAGE U _N IN VOLTS | 440/3PHASE |
| RATED FREQUENCY f _N IN Hz | 50 |
| TEMPERATURE CATEGORY | -40/D |
| DISCHARGE DEVICE | Ext. Fitted |
| REFERENCE OF SELF HEALING DESIGN | MPP (SH) |
| CONNECTION SYMBOL | Delta (△) |
| INTERNAL FUSES | No |
| INDICATION OF OVERPRESSURE OR THERMAL DISCONNECTOR | Provided |
| INSULATION LEVEL U; IN kV | 3Kv |
| REFERENCE TO IEC 60831 | IEC 60831-1 |



<u>CONCLUSION:</u> Place and date of inspection at Shreem Electric limited located in Kolhapur, India on 14/08/2021 and the sample test performed by manufacturer from 14/08/2021 to 20/08/2021. Sample test witnessed by our SAI inspector in laboratory of the manufacturer and concluded that the goods are in conformity with standard No.: EN 60831-1

Furthermore, We confirm that the test report is acceptable and the manufacturer's laboratory found to be as qualified.

Manufacturer's Representative

S.A.I. Representative

MPP Div.
Gat No. 311
Near R.K.Market
Yard Gate
Jaysingpur - 416 144,
Dist.: Kolhapur, Maharashtra, (INDIA)

Tel : +91-2322-221021/22/24/45

Fax : +91-2322-221023 e-mail : info@shreemelectric.com Web : www.shreemelectric.com