

TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1

TEST DATE:

14/08/2021 -20/08/2021P/I NO. : IR-20210523-2 dtd:23.05.2021

PRODUCT: 25 KVAR, 440V, 3PH, 50Hz, NORMAL DUTY MPP TYPE CAPCITOR UNITS.

Sr. No.	REQUIREMENT /TEST	SPECIFICATIONS	RESULT	REMARK
1.	K∨AR Rating	25 K∀AR	25 KVAR	PASS
2.	Voltage Rating	440 V	440 V	PASS
3.	Basic Mfd Value (in Mfd)	205.62 µfd	205.62 µfd	PASS
4.	Sr. No. of the Capacitor	A882000	A882000	PASS
5.	Capacitor Type	NORMAL DUTY	NOR MAL DUTY	PASS
6.	Frequency	50 Hz or 60Hz	50Hz	
71.	Capacitance Measurement and Output Calculation before ${\rm HV}$	-5% to +15% for units and banks upto 100 KVAR	207.1 µfd	PASS
7.2	Capacitance Measurement and Output Calculation after HV	0% to 10% for units and banks above 100 KVAR	207.1 µfd	PASS
8.	Measurement of the tangent of the loss angle (tan δ) of the capacitor	S hall not exceed value declared by manufacture	0.47 Watt/k∀Ar	PASS
9.	Voltage tests between Terminals (High Voltage test)	2.15 X R ated Voltage for 2 sec	Withstood	PASS
10.	Voltage tests between terminals and container	3 K∨AC for 10 Sec	Withs tood	PASS
11.	Test of internal discharge device	In 3 min reduces to 75 \lor or less	43 Sec	PASS
12.	Sealing Test (Leakage Test)	75°C for 2 Hrs	No Leakage	PASS
13.	Guide for Installation and Operation ofL.T. Power Capacitors: The installation manual attached herewithGeneral Choice of rated Voltage Operating temperature Installation High Ambient air temperature Evaluation of losses Special Service conditions Over voltages Overload currents 		The Installation manual attached	PASS



Tel	:	+91-2322-221021/22/24/45
Fax	:	+91-2322-221023
e-mail	:	info@shreemelectric.com
Web	:	www.shreemelectric.com
	:	





TEST REPORT

REPORT NO. IN 42804 VOC STANDARD NO: EN 60831-1 TEST DATE: 14/08/2021 -20/08/2021P/I NO. : IR-20210523-2 dtd:23.05.2021

PRODUCT: 25 KVAR, 440V, 3PH, 50Hz, NORMAL DUTY MPP TYPE CAPCITOR UNITS.

RATING PLATE DETAILS

MANUFACTURER	M/s. SHREEM ELECTRIC LTD
IDENTIFICATION NUMBER AND MANUFACTURING YEAR	A882000 08-2021
RATED OUTPUT Q _N IN KVAR	25Kvar
RATED VOLTAGE U _N IN VOLTS	440/3PHASE
RATED FREQUENCY f _N IN Hz	50
TEMPERATURE CATEGORY	-40/D
DISCHARGE DEVICE	Ext. Fitted
REFERENCE OF SELF HEALING DESIGN	MPP (SH)
CONNECTION SYMBOL	Delta (△)
INTERNAL FUSES	No
INDICATION OF OVERPRESSURE OR THERMAL DISCONNECTOR	Provided
INSULATION LEVEL Ui IN kV	3Kv
REFERENCE TO IEC 60831	IEC 60831-1



CONCLUSION: Place and date of inspection at Shreem Electric limited located in Kolhapur,India on 14/08/2021 and the sample test performed by manufacturer from 14/08/2021 to 20/08/2021-. Sample test witnessed by our SAI inspector in laboratory of the manufacturer and concluded that the goods are in conformity with standard No.: EN 60831-1

Furthermore, we confirm that the test report is acceptable and the manufacturer's laboratory found to be as qualified. S.A.I. Representative

Manufacturer's Representative





Tel +91-2322-221021/22/24/45 +91-2322-221023 Fax e-mail info@shreemelectric.com . Web www.shreemelectric.com